Betore Starting Work.

WORK AREA

- 11
- Do not use this diamond drill rig where there is a danger of explosion. Where there is a danger of explosion. Where there is a danger of explosion, or cylinders. Make sure that the area is clear and aste and hat no-one is near to you or could distract you. Protect other people from the noise, and debris. Warn others to keep away. Put barriers around your work ages. **.**2
- 3.
- 'Pair
- °t
- 'G
- Leas. Check that there are no hidden where you are drilling. Check you have an adequate, clean water supply either from the mains or trom a water tank. Make sure the waste water will not case damage. Check if the water case damage. Check if the water company supplied water collection equipment, use it. .9

- **СРЕВАТОРЗ**
- The following items of personal protective equipment (ppe) are the minimum that should be worn whenever you use this machine. Particular jobs or environments may require a higher level of protection.
- **'**Z
- 31
- You must wear impact resistant you must wear impact resistant grade 1) when you are working with This equipment is likely to cause appropriate ear mufts or plugs giving noise levels up to 86 dB(A) wear appropriate ear mufts or plugs giving minimum.
- °t

- You will need to wear an appropriate dustmask (with a minimum of EN149 dustmask (with a minimum of EN149 protection) to protect yourself from spray, mist or dust. Mill also need to wear appropriate personal protective equipment.

Check your machine, cables and plugs and all other equipment. If anything is found damaged, do not

3YT TEB Iludilos

The Crescent Birmingham Business Park

Association Europe

0515 Safety Guidance

It is important to read this entire leaflet

BEFORE using the Diamond Drill Rig

1. Electricity is dangerous and must always be used with

water away from electrical parts.

concrete, masonry or stone.

careful and controlled way.

Water and electricity are a hazardous combination. Keep

This diamond drill rig is designed to drill large diameter

holes in floors, walls and ceilings through reinforced

impact resistant goggles: EN166 - B or BS2092 grade 1;

ear muffs or plugs giving protection for levels up to 86 dB(A);

:lism3

:euoudeie

сове рыгга

dust mask - a minimum of EN149 FFP3(s) protection;

rcd if using a 230 volt (mains) supply.

44 (0) 121 380 4600 44 (0) 121 333 4109 mail@hae.org.uk

Umin. Use only the correct grade core drills company for the material being cut company for the material being cut. Make sure that your core drill in fong enough to go right through the wall core: of the brick or masonry core: of the brick or masonry temains inside the core drill until you core: of the brick or masonry core of the br

Switch the diamond drill rig off, and unplug it before changing the core drill.

Make sure you understand all of the controls. Before you switch the diamond drill rig on, you must know how to stop it.

Your machine may operate at more than one speed and you may be able to set the core drill to rotate clockwise or anticlockwise. Ensure you have the right settings before you start work.

Them. Machines with a cylindrical yellow industrial plug fitted are designed to industrial plug fitted are designed to tun off a special 10% supply. The power the machine from a normal mains 230% supply if a portable transformer has been supplied, take transformer has been supplied. The transformer has been supplied, take transformer has been supplied. The power the machine are been supplied to the solution are been supplied. The transformer has been supplied are to the destribution are been supplied. The transformer has been supplied are been to the transformer has been supplied. The transformer has been supplied are been to the transformer has been supplied. The transformer has been supplied are been to the transformer has been supplied. The transformer has been supplied are been supplied are been to the transformer has been supplied. The transformer has been supplied are been supplied are been to the transformer has been supplied. The transformer has been supplied are been supplied are been supplied. The transformer has been supplied are be

Check that the plug on your machine matches your supply. Do not try to force connections or improvise them.

use the diamond drill rig - contact the hire company.

areat care.

task

aloves:

or alcohol.

2.

6.

7.

8.

9

121 380 4600

e.org.uk

44 (0) 121 333 4109

www.hae.org.uk

If you need to use an extension cable, follow any special instructions given by the hire company. If the hire

110 VOLT MACHINES (YELLOW PLUG)

Your machine will only operate on one voltage: it will be 110 vor 230v. 110v reducting blug fitted. 230v evaporative air coolers will have either a normatival plug. Fead the instructions below for your evaporative air cooler.

anchoring. If you are core drilling into walls or celling, then you must additionally brace or anchor the rig.

If you are core drilling straight into a smooth floor, the vacuum clamp on the machine will normally be strong enough to hold the rig firm. If you are core drilling the floor at an angle, then your rig will need to be arrither secured by bracing or arrithma.

have drilled through. Make sure that people on the other adde of the wall or floor vou are drilling are safe from the core, or any you break through. Stop the machine and unplug before from the core drill. from the core drill.

ВИАСИИЕ АИР АИСНОВИИЕ

Sh.

If you are using a portable transformer directly into the 230v socket. Do not use any 230v extension cables. If you need to use any

ELECTRICAL SAFETY

.S.

31

.2

1

'G

.4

Diamond Drill Rig

The rules and procedures in force where people are at work may require the person responsible for this equipment to carry out a specific risk assessment.

The action of this drill can cause injury or damage if the machine is not used in a

If you have not used a diamond drill rig before, familiarise yourself with the

machine first. Practice on some straightforward job before you start on the main

Plan your work and think ahead to make sure you will always be working safely. You must have at least the following items of personal protective equipment:

This machine must not be used by minors, or by anyone under the influence of drugs

This diamond drill rig is designed for operation by an able bodied adult. Anyone with either temporary or permanent disability must seek expert advice before using it.

Every effort has been made by HAE/EHA to ensure that the information given in this document and supporting mat is accurate and not misleading. HAE/EHA cannot accept responsibility for any loss or liability perceived to have arisen from the use of any such document/material. Only Acts of Parliament and Statutory Instruments

3

.2

1

'G

·Þ

3

.2

.meni

have the force of law and only the courts can authoritatively interpret the law.

For guidance on managing

construction health risks go to

www.hse.gov.uk/construction

Using the Diamond Drill Rig

Do not disconnect any water hose until you have switched off, unplugged the drill,

Make sure your core drill is long enough to go right through the wall or floor or

If you think the cable may be cut or damaged in any way, switch off and unplug

at the mains before inspecting it. If the cable attached to the diamond drill rig is

damaged, stop using the machine. Contact the hire company. If an extension

10. Switch off and remove the plug from the socket before leaving the diamond drill

11. If your equipment does not work properly do not attempt to repair it. Contact the

Please keep this leaflet safely as it may be required for future reference

©Copyright Hire Association Europe April 2011

Any unauthorised reproduction – manually or electronically – is STRICTLY prohibited

12. You may want to read this leaflet again. Please keep it until you finish work.

Keep the core drill rotating while you are drilling and when withdrawing it.

Keep the cable clear of the core drill and any sharp edges on your work.

Wear your protective equipment including dust mask and goggles.

Ensure you have adequate water flow to the core drill when drilling.

Check you are not going to drill into any hidden cables or pipes.

and turned off any water tap or valve to stop the flow.

the core drill will 'bottom' and will not drill any further.

Take care not to accidentally pull the plug from the socket.

Hire Accordiation Euro

and safe.

Make

•t

.s

esU .r

31

2450 Regents Court

Birmingham Bus Solihull B37 7YE

The Cr

connections are dry Make sure that any

Make sure that any could catch fire. Make sure that and perity of the stension cable out carefully doorways or windows where it might over it. Unroll it fully or vehicles might run could catch fire.

Lay the extension cable out carefully instructions supplied with it. It you need an extension cable, by the fine company. If the fine company have not given any special instructions, you should only use a instructions, you should only use a longer than 50 metres (160 feet). Pung it directly into the rcd.

Instructions supplied with it.
Instructions supplied with it.
Instructions supplied with it.

Make sure that any extension cable connections are dry and safe.

Leave and any more any more and contraction and the more and the strength of t

company have not given any special instructions, you ark frouid only use a suitably rated heavy duty 110v extension cable, not longer than 50 metres (160 feet). You must only use an extension cable out carefully transformer and the machine.

(золяяе рім ов веле рела) 230 VOLI MACHINES

cable has been damaged, do not use it again.

1. 2.

3.

4.

5.

6.

7.

8

9.

rig unattended.

hire company.

DIAMOND DRILL RIG

ANDARA TOOLS AND