

## FLEX-Elektrowerkzeuge GmbH

Bahnhofstrasse 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

# FLEX

## Wall and ceiling sanders

### WST 700 VV Plus

Order no. 350.338



#### Vario-Giraffe® wall and ceiling sander

- VV electronic control: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- Using a unique telescopic system, the Vario-Giraffe® adapts to your needs. Length adjustable from 1330 mm - 1730 mm. Open telescope lock lever, pull out handle and close lever. Handle rotates through 360°
- Adjustable locking screw for telescopic extension
- Ergonomic design with many different handling possibilities for fatigue-free working. The motor is always kept between the gripping positions, ensuring a perfect balance
- Fitted with interchangeable heads that are attached and removed with a click.
- Including triangular sander head. This is optimally suited to sanding corners and edges. The random orbital movement of the sanding head takes the abrasive right up to the edges
- Backing pad with hook and loop face
- The articulating sanding head can be adjusted to every tilt and angle.
- Vacuum cleaning system: guard with a brush ring, flexible suction hose from the sanding head to the guide tube. Connection facility at the rear of the telescopic tube for FLEX industrial vacuum cleaner
- Effective dust extraction from between the brush ring and the sanding pad (round) and through the 10-hole extraction ports prevents premature clogging of the abrasive and promotes a healthy, dust-free working environment
- The brush ring is spring-mounted so that the round sanding head accurately follows all uneven contours. This allows the head to be applied with fingertip precision and also prevents any dust escaping
- Ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting, polishing.
- This machine is also available in 110 V

| Technical attributes        | WST 700 VV Plus |
|-----------------------------|-----------------|
| Power input                 | 710 watt        |
| Power output                | 420 watt        |
| No load speed               | 1000-1500 rpm   |
| Corner sander no-load speed | 3000-4500 rpm   |
| Dimensions in mm            | 1330-1730       |
| Weight                      | 4,8 kg          |

| Standard equipment  |                     |
|---|---------------------|
| Triangular sanding head   | 350.354             |
| Round sanding head with velcro sanding pad soft   | 350.346             |
| Velcro backed abrasive paper, Select, 1 x P 60, 80, 100, 220                                  |                     |
| Velcro sand paper, angular, 1 x P 60, 80, 100, 220  | 1 item from 348.570 |
| 1 soft sanding pad  |                     |
| 1 hexagon socket screw key, special tool 5  |                     |
| Antistatic suction hose 32 mm Ø x 4 m with snap coupling and coupling bush for vacuum cleaner | 354.953             |
| Carry case  | 1 piece             |