

## Technical Data

Accuracy	Positioning accuracy: $\pm 2\text{mm}$ @ 200mm wall thickness Thickness measuring accuracy: $\pm 5\%$ of wall thickness
Measuring range	5 cm - 135 cm
Position-finding accuracy, standard	$\pm 8\text{ mm}$ per 200 mm wall thickness
Position-finding accuracy, maximum (no influence of metal)	$\pm 2\text{ mm}$ per 200 mm wall thickness
Accuracy wall thickness measurement	$\pm 5\%$
Disclaimer	Accuracy may be significantly reduced by irregular positioned reinforcing bars, welded reinforcing mesh, sheet metal or other metal objects close to the tool. Please refer to the operating instructions for details
Battery life (alkaline)	17 h
Dimensions PX 10 (LxWxH)	PX10T: 160 x 95 x 33 mm PX10R: 210 x 95 x 33 mm
Weight PX10T	240 g
Battery type	1 x 9 V
Weight PX10R	275 g
Operating Temperature Range	-20 - 55 °C
Max. measuring distance	135 cm
IP protection class	IP 56
Additional Product Info	*Accuracy may be significantly reduced by irregularly positioned reinforcing bars, welded reinforcing mesh, sheet metal or other metal objects close to the tool
Package Contents	PX 10 with P1X 10 T transmitter, PX 10 R receiver, 2 x PDA 60 hand straps, PUA 91 adhesive Putty, PUA 92 adhesive Strips, 2 x 9v alkaline batteries, PX 10 operating instructions, 2 x producer certificates. Supplied in an impact-resistant plastic tool case.